

# COMANCHE GEAR



10340 REGENT CIRCLE ∞ NAPLES, FL 34109  
 PHONE & FAX 239/593-6944 ∞ CELL 239/404-7524  
[MKURKE@COMANCHEGEAR.COM](mailto:MKURKE@COMANCHEGEAR.COM)

		<b>Pressure Type Wire Connector Chart</b> <b>AMP* SOLISTRAND* Terminals</b> <b>and Splices (Use Type "W" Tooling)</b>		<b>408-2049</b> 30 MAY 00 Rev H TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS <b>CU</b>	
<b>AMP WIRE RANGE</b>	<b>424C LISTED</b>	<b>LR 7189 CERTIFIED</b>			
22-16 Solid or Stranded	22-16 Solid or Stranded	22-16 Solid or Stranded			
16-14 Solid or Stranded	16-14 Solid or Stranded	16-14 Solid or Stranded			
12-10 Solid or Stranded	12-10 Stranded	12-10 Solid or Stranded			
8 through 600 MCM Solid or Stranded	8 through 600 MCM Stranded	8 through 4/0 Solid or Stranded			

**NOTE:** 22-16 terminals and splices are stamped 22-18 in accordance with MIL-T-7928.  
**DANGER:** Not to be used on aluminum wire – may cause equipment failure leading to serious injury or death.

©2000 Tyco Electronics Corporation, Harrisburg, PA.      TOOLING ASSISTANCE CENTER 1-800-722-1111      LOC B  
 \*Trademark All International Rights Reserved.      AMP FAX/PRODUCT INFO 1-800-522-6752      Revised per EC 0990-0552-00

**THIS IS THE UN-INSULATED BUTT SPLICE USED IN THE NOSE GEAR PORTION OF YOUR WIRING HARNESS KIT.**



**THIS IS THE "TYPE W" TOOLING REFERRED TO IN THE AMP LITERATURE ABOVE WHICH IS THE SUGGESTED TOOL TO CRIMP THE BUTT SPLICES AT THE NOSE GEAR HARNESS. THIS TOOL IS AVAILABLE FOR LOAN; A VERY LIMITED QUANTITY AVAILABLE FOR PURCHASE - GOOD SERVICEABLE CONDITION - \$50, BUT THAT CAN CHANGE DEPENDING ON THE SUPPLY AND MY COST.**